

M-1002 and Q-1002

VHF Belt Transmitter and VHF Handheld MIC/Transmitter



Specifications: M-1002

Frequency Range	VHF High Band 160 - 260 MHz
Switchable Frequencies	1
RF Power Output	< 30mW
Spurious Emission	> 40 dB below carrier
Dynamic Range	> 110 dB
Display Screen	LED
T.H.D.	< 0.5%
Battery Type	9V x 1
Operating Life	about 16 hours (Alkaline)
Charging Function	-
Peak Deviation	± 15KHz
Antenna	Built in
Connector	Dynamic/Condenser type
Dimensions	100(L) x 66(W) x 24(H) mm 3.94 (L) x 2.60 (W) x 0.95 (H) in
Weight	90 g / 3.17 oz

Specifications: Q-1002

Frequency Range	VHF High Band 160 - 260 MHz
Switchable Frequencies	1
RF Power Output	< 30mW
Spurious Emission	> 40 dB below carrier
Dynamic Range	> 110 dB
Display Screen	LED
T.H.D.	< 0.5%
Battery Type	9V x 1
Operating Life	about 16 hours (Alkaline)
Charging Function	-
Peak Deviation	± 15KHz
Antenna	Built in
Microphone Capsule	Dynamic/Condenser type
Dimensions	Φ 46 x 240L mm Φ 1.81 x 9.45 in
Weight	195 g / 6.87 oz